

Customer Ref:
Date Ordered:
Date Required:
Previous Quote No:

Invoice Name & Address:

Telephone:

Delivery Address (if different to Invoice Address):






NOTE: Site deliveries may incur a surcharge

Secured By Design: ☐ Doc Q Compliant: ☐
(Internally glazed only)
U Value Compliant: ☐
BFRC Energy Rated: A+ ☐ A ☐ B ☐ C ☐
I am an Authorised Retailer- AR No:

SYSTEM <i>ch = Chamber</i> TOTAL70C 5ch <input type="checkbox"/> 6ch* <input type="checkbox"/> *6ch available in white only TOTAL70S 5ch <input type="checkbox"/>	FRAME CONSTRUCTION Internally Beaded <input type="checkbox"/> Externally Beaded <input type="checkbox"/> Ext'l Mech <input type="checkbox"/> BEAD Bevel <input type="checkbox"/> Ogee <input type="checkbox"/> GASKET COLOUR Black <input type="checkbox"/> White <input type="checkbox"/> Grey <input type="checkbox"/> Black out/White in <input type="checkbox"/>	FRAME COLOUR <i>NOTE Mahogany only available on 70C</i> White only <input type="checkbox"/> Other (specify colour): <input type="text"/> On White <input type="checkbox"/> LOCKING SYSTEM Espag <input type="checkbox"/> S/Bolt <input type="checkbox"/> HANDLE COLOUR White <input type="checkbox"/> Gold <input type="checkbox"/> Black <input type="checkbox"/> Chrome <input type="checkbox"/> Satin <input type="checkbox"/>
---	--	---

Item	O/All Size		Qty	Mullion Break	Transom Drop	Glass Supplied		Glass Description	Spacer Bar Colour*	Outer Frame			Add on/ Coupler	Cill Type	Cill Length	Drainage		Hinge Type ±			Sash Security Lock	Head Drip		Slot Vent	
	Width	Height				Yes	No			52	62	72				Base	Face	Egr	Rest	Small		Large	Head	Sash	
1																		Minimum mullion split to achieve Building Regs Fire Escape is 605mm using small outer frame and mullion.							
2																									
3																									
4																									
5																									

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

1	2	3	4	5
				

Special Requirements: 	Ordering Notes: TOTAL70C = Bevelled System, 5 and 6 chamber options. TOTAL70S = Fully Sculptured, 5 chamber system. Frame sizes should be entered as overall including add on's and cills. Internally beaded windows are <u>not</u> available with mechanical joints. Glazing: 70mm System: 28mm double glazing or 32mm, 36mm & 44mm triple glazing. Gasket Types: Security gasket will be fitted as standard to externally beaded windows. *Spacer Bar: Bronze as standard or black if warm edge spacer bar required. *Hinge Types: Egr = Egress Hinge (sidehung only) - Add EC for Easy Clean or NC for Non Clean Rest = Restrictor Hinge. If standard hinges are required leave blank.	Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below. Signed :
--	--	--

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.