

1-5 Fletchers Square, Temple Farm Ind Estate,  
Sutton Road, Southend-on-Sea,  
Essex SS2 5RN  
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name & Address:

Telephone:

Customer Ref:

Date Required:

Previous Quote No:

Works Order No:

Date Received:

Secured By Design ☐ Doc Q compliant ☐

U Value Compliant: ☐

BFRC Energy Rated: B ☐

Authorised Retailer - Energy Rated Product

AR No:  B ☐

FRAME CONSTRUCTION—Internally (dummy sashes will be reqd) or Externally Glazed System

Outer: AW605 53x58mm ☐ AW601 53x70mm ☐ Sash: AW614 45mm Int glazed ☐ AW611 56mm Ext glazed ☐ Trans/Mull: AW632 57mm

GLAZING BEAD/GASKET TYPE *\*Bead type determined if int/ext glazed*

Bead\*: Square or Bevel Gasket: Black ☐ Anthracite Grey ☐

FRAME FINISH

White (RAL9910 Std) ☐ RAL:  on White ☐

HANDLE COLOUR

White ☐ Gold ☐ Black ☐ Chrome ☐ Satin ☐ Grey ☐

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description	Spacer Bar Colour*	Add on/ Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from OUTSIDE – including Tilt & Turn Windows

\*\*Std cill length = frame width +100mm

12345

Special Requirements:

Ordering Notes:

Glazing: 28mm glazing as standard \*Spacer Bar: Bronze as standard or black if warm edge spacer bar required.

Min/Max Heights: Min Height & Width = 350mm / Max Height = 1500mm, Max Width = 1250mm

Transom/Mullion: AW632 will be used on these windows

Cill Height: 25mm \*\*Cill sizes available: 95 / 150 / 190mm

Locks: Shootbolt locking as standard

Frame Add On: 20mm only Coupler: 15mm & 26mm available

Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :

Please do not write in the white space around the form. Use special requirements box for any further information.

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.