

Customer Ref: _____
Date Ordered: _____
Date Required: _____
Previous Quote No: _____

Invoice Name & Address: _____

Telephone: _____

Delivery Address (if different to Invoice Address): _____

NOTE: Site deliveries may incur a surcharge

Secured By Design: ☐ Doc Q Compliant: ☐
Calibre Casement Windows Only
U Value Compliant: ☐
BFRC Energy Rated: A ☐ B ☐ C* ☐
*Only available with 67mm Outerframe
I am an Authorised Retailer- AR No: _____

SYSTEM
Calibre 5 Chambers

FRAME CONSTRUCTION
Internally Beaded Only

SASH TYPE
Bevelled Only

BEAD
Ogee Only

GASKET COLOUR
Integral Black Gasket Only

FRAME COLOUR
White ☐ Rosewood on White ☐ Oak on White ☐






LOCKING SYSTEM
Espag (Default) ☐ S/Bolt ☐

HANDLE COLOUR
White ☐ Gold ☐ Black ☐ Chrome ☐ Satin ☐

IMPORTANT NOTE:
If you require a window specification that is different to that shown on this form, please enquire about the other window systems we manufacture.

Item	O/All Size		Qty	Mullion Break	Transom Drop	Glass Supplied		Glass Description	Spacer Bar Colour*	Outer Frame		Add on/ Coupler	Cill Type**	Cill Length	Drainage		Hinge Type *		Sash Security Lock	Head Drip		Slot Vent		
	Width	Height				Yes	No			55mm	67mm				Base	Face	Egr	Rest		Small	Large	Head	Sash	
1																	Minimum mullion split to achieve Building Regs Fire Escape is 605mm using small outer frame and mullion.							
2																								
3																								
4																								
5																								

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

1	2	3	4	5
				

Special Requirements: _____

Ordering Notes:
Frame sizes should be entered as **overall** including add on's and cills.
Frame Extenders: 20mm and 50mm available only
***Spacer Bar:** Bronze as standard or Black if warm edge spacer bar required.
****Cills:** 95mm, 150mm, 180mm & 225mm Cills available
***Hinge Types:** Egr = Egress Hinge (sidehung only) - Add **EC** for Easy Clean or **NC** for Non Clean
Rest = Restrictor Hinge. If standard hinges are required leave blank.
Glazing: 28mm glazing only

Important:
Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.
Signed : _____