

Please do not write in the white space around the form. Use special requirements box for any further information.



ORDER FORM - REHAU Rio Flush Sash Window

Tel: 01702 613733 / Fax: 01702 613367
www.climatec-windows.co.uk

Page of

Customer Ref:
Date Ordered:
Date Required:
Previous Quote No:

Invoice Name & Address:

Telephone:

Delivery Address (if different to Invoice Address):

NOTE: Site deliveries may incur a surcharge

Manufacturing Type:
Welded Sash/Frame ☐
Mechanical Sash/Frame° ☐
ETL Sash and ETL Frame (max frame width 2560mm) ☐
Additional options:-
Mechanical Sash/Frame° with DBR ☐
ETL Sash and Welded Frame ☐

OUTER FRAME SYSTEM: TOTAL70C ☐ TOTAL70S ☐ **BEAD TYPE:** Mitred** ☐ Scribed ☐ **JOINT FINISH** If white profile, please choose: Grooved ☐ Knifed ☐

COLOUR: White ☐ White Grain ☐ Clotted Cream ☐ Chartwell Green ☐ Turner Oak ☐ Golden Oak ☐ Rosewood ☐ Pearl Grey ☐ Black Brown ☐ Anth Grey (grained) ☐
Anth Grey (smooth) ☐ Slate Grey (grained) ☐ Midnight Black ☐ Pebble Grey (grained) -Total70C only ☐ Sage (Smooth) -Total70C only ☐ Both Sides ☐ On White ☐

HANDLE TYPE & COLOUR: *Please see spec sheets on our website for handles styles & colours* **STANDARD:** ☐ Colour: **TRADITIONAL:** ☐ Handle Type: Colour:
CONTEMPORARY: ☐ Handle Type: Colour: Extras: Peg & Stay Dummy ☐ Dummy Butt Hinges ☐

BEAD OPTION: 28mm Deco ☐ 28mm Square ☐ 32mm Flat ☐ 34mm Raised ☐ **OTHER:** Doc Q: ☐ U Value Compliant: ☐ BFRC Rating: A ☐ A+ (triple glazed only) ☐ Auth Retailer No:

Item	O/All Size		Qty	Mullion Break	Transom Drop	Glass Supplied		Glazing Thickness* (see below)	Glass Description	Spacer Bar Colour	Outer Frame			Add On/ Coupler	Std Cill Type					55mm Rad Cill	Cill Length	Drainage		Hinge Type		Hinge Guard	Doc F Slot Vents		
	Width	Height				Yes	No				52	62	72		None	95	150	180	225	165		Base	Face	Rst	Egr		62mm/72mm Head	Sash	Over Head
1																													
2																													
3																													
4																													
5																													

1	2	3	4	5

Special Requirements:

Ordering Notes: VIEW ALL WINDOWS FROM OUTSIDE
°Mech sash and frame only available on 52mm & 62mm outer frame / Not available on 72mm outer frame
**Mitred bead is not available with full mechanical sash
Yale Shootbolt locking system with night vent facility
Hinge Type: **R**=Restrictor **Egr** = Egress Hinge (sidehung only) - Add **EC** for Easy Clean or **NC** for Non Clean
*28mm unit = 4/20/4 soft coat inner, black warm edge spacer bar, 90% argon gas. Deco or Flat Bead
*32mm unit = 4/10/4/10/4 soft coat x2, black warm edge spacer bar, 90% argon gas. Flat Bead
*34mm unit = 4/10/4/12/4 soft coat x2, black warm edge spacer bar, 90% argon gas. Raised Deco Bead
All fixed panes supplied as dummy sashes as standard. All Transoms/Mullions supplied as mechanical

Important:
Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :

03025R5RSJ-9809

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.