

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Customer Ref:

Date Ordered:

Date Required:

Previous Quote No:

Invoice Name & Address:

Telephone:

Delivery Address (if different to Invoice Address):

NOTE: Site deliveries may incur a surcharge

Tel: 01702 613733 / Fax: 01702 613367
www.climatec-windows.co.uk

Secured By Design: - Single Doors only

SYSTEM

TOTAL70C TOTAL70S

FRAME CONSTRUCTION

Welded frame/welded sash Welded frame/ETL sash ETL frame/ETL sash ETL frame/Welded sash

JOINT FINISH

If white profile, please choose: Grooved Knifed

FRAME COLOUR

White only Other (specify colour): On White

Opening & Handing / Master

Open Out Left Hung (M) Right Hung (M)

Outer Frame Bottom

Std Frame Slim Frame Low Ali OUM70 OUM70 (sub cill) Silver Gold Optional Int Ramp

Cill Type

None 95mm 150mm 180mm 225mm 165 x 55mm Not available in all colours

Drainage

Concealed Drain Face Drain None

Handle Type & Colour

Lever/Lever Lever/Lever (Scrolled) Lever (in)/Blank (out) White Gold Black Chrome Satin Enduro Steel Grey

Hinge Type

SFS 3D Butt Hinge Matt Black White

Bead Option

28mm Deco 28mm Square

Letter Box Note: Style 702 & 703 Only

Slimline Satin Premium White Gold Black Chrome Brushed

Glazing

Unglazed Double Glazed Triple Glazed* U Value Compliant

Glass Description:

Spacer Bar Colour**:

Extras

Head Drip: Small Large Ultion Cylinder As standard Thumbturn 90o Door Restrictor

Overall Frame Size

Width: Midrail Height (inc cill): Height: Sash Width:

Doc F Slot Vents: Head Sash Overhead

Please note on drawing if specific location required Viewed from Outside

Frame Add On's 70mm: 15mm, 45mm, 65mm

Top

Bottom

Left

Right

Please indicate coupler required should frame have to be split:

70mm System 2mm 3mm 10mm 10mm HD 10mm HD Extra 24mm

Ordering Notes:

"TOTAL70C" = Bevel System; 5 chamber frame. "TOTAL70S" = Sculptured System, 5 chamber frame. Combination frames will be made using large outerframe unless specified. Please indicate coupler required. Frame sizes & midrail heights should be entered as overall including add on's and cills.

*Glazing: 28mm unit = 4/20/4 soft coat inner, black warm edge spacer bar, 90% argon gas. Deco or square bead 28mm triple glazed unit = 4/10/1.1/8/4 soft coat x2, black warm edge spacer bar, 90% argon gas. Deco or square Bead

**Spacer Bar: Bronze as standard or black if warm edge spacer bar required.

Mobility: Only meets Part 'M' requirements when the overall threshold design is specified correctly. Doc M is not available with thresholds on cills.

Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed. Signed:

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.