Climatec
Windows & Doors

ORDER FORM - CALIBRE CASEMENT WINDOW

Tel: 01702 613733 / Fax: 01702 613367
www.climatec-windows.co.uk

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Customer Ref:
Date Ordered:
Date Required:
Previous Quote No:

Invoice Name & Address:
Telephone:

Delivery Address (if different to Invoice Address):
NOTE: Site deliveries may incur a surcharge

Secured By Design: ☐ Doc Q Compliant: ☐
Calibre Casement Windows Only

U Value Compliant: ☐

BFRC Energy Rated: A ☐ B ☐ C* ☐
*Only available with 67mm Outerframe

I am an Authorised Retailer- AR No:

SYSTEM	FRAME CONSTRUCTION	SASH TYPE	BEAD	GASKET COLOUR
Calibre 5 Chambers	Internally Beaded Only	Bevelled Only	Ogee Only	Integral Black Gasket Only

IMPORTANT NOTE:
If you require a window specification that is different to that shown on this form, please enquire about the other window systems we manufacture.

FRAME COLOUR			LOCKING SYSTEM		HANDLE COLOUR					
White ☐	Rosewood on White ☐	Anthracite Grey (grained) on White ☐	Espag (Default) ☐	S/Bolt ☐	White ☐	Gold ☐	Black ☐	Chrome ☐	Satin ☐	Enduro Steel ☐

Item	O/All Size		Qty	Size from edge of frame (not add ons)		Glass Supplied		Glass Description	Spacer Bar Colour*	Outer Frame		Add on/ Coupler	Cill Type**	Cill Length	Drainage		Hinge Type ±			Hinge Guards	Head Drip		Doc F Reg Slot Vents	
	Width	Height		Mullion Break	Transom Drop	Yes	No			55mm	67mm				Base	Face	Egr	Minimum mullion split to achieve Building Regs Fire Escape is 605mm using small outer frame and mullion.	Rest		Small	Large	Head	Sash
1						☐	☐			☐	☐				☐	☐	☐		☐	☐	☐	☐	☐	☐
2						☐	☐			☐	☐				☐	☐	☐		☐	☐	☐	☐	☐	☐
3						☐	☐			☐	☐				☐	☐	☐		☐	☐	☐	☐	☐	☐
4						☐	☐			☐	☐				☐	☐	☐		☐	☐	☐	☐	☐	☐
5						☐	☐			☐	☐				☐	☐	☐		☐	☐	☐	☐	☐	☐

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

1	2	3	4	5

Special Requirements:

Ordering Notes:
Frame sizes should be entered as **overall** including add on's and cills.
Frame Extenders: 20mm and 50mm available only
***Spacer Bar:** Bronze as standard or Black if warm edge spacer bar required.
****Cills:** 95mm, 150mm available. 180mm & 225mm Cills are available in Rehau only.
±Hinge Types: **Egr** = Egress Hinge (sidehung only) - Add ***EC*** for Easy Clean or ***NC*** for Non Clean
Rest = Restrictor Hinge. If standard hinges are required leave blank.
Glazing: 28mm glazing only

Important:
Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :

0325C—Issue 10 09/25

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.