Climatec
Windows & Doors

ORDER FORM - REHAU CASEMENT WINDOW

Tel: 01702 613733 / Fax: 01702 613367
www.climatec-windows.co.uk

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Customer Ref:
Date Ordered:
Date Required:
Previous Quote No:

Invoice Name & Address:

Telephone:

Delivery Address (if different to Invoice Address):

NOTE: Site deliveries may incur a surcharge

Secured By Design: ☐ Doc Q Compliant: ☐ *(Internally glazed only)*

U Value Compliant: ☐

BFRC Energy Rated: A+ ☐ A ☐ B ☐ C ☐

I am an Authorised Retailer- AR No:

SYSTEM **6ch avail in white only*
TOTAL70c 5ch ☐ 6ch* ☐
TOTAL70s 5ch ☐

FRAME COLOUR White only ☐ Other *(specify colour)*: On White ☐ ***NOTE*** *Mahogany only available on 70C*

FRAME Int Beaded

BEAD Bevel - Black ☐ Ogee - Black ☐

LOCKING SYSTEM Espag ☐ S/bolt ☐

HANDLE TYPE & COLOUR:
Please see spec sheets on our website for handles styles & colours

STANDARD: ☐ Colour:

TRADITIONAL: ☐ Handle Type: Colour:

CONTEMPORARY: ☐ Handle Type: Colour:

Extras: Peg & Stay Dummy ☐

Item	O/All Size Width	O/All Size Height	Qty	Size from edge of frame (not add ons) Mullion Break	Size from edge of frame (not add ons) Transom Drop	Glass Supplied Yes	Glass Supplied No	Glass Description	Spacer Bar Colour*	Outer Frame 52	Outer Frame 62	Outer Frame 72	Add on/ Coupler	Cill Type	Cill Length	Drainage Base	Drainage Face	Hinge Type ± Egr	Hinge Type ± Rest	Hinge Guard	Head Drip Small	Head Drip Large	Doc F Reg Slot Vents Head	Doc F Reg Slot Vents Sash	Doc F Reg Slot Vents Over Head
1						☐	☐			☐	☐	☐				☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
2						☐	☐			☐	☐	☐				☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
3						☐	☐			☐	☐	☐				☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
4						☐	☐			☐	☐	☐				☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
5						☐	☐			☐	☐	☐				☐	☐	☐	☐	☐	☐	☐	☐	☐	☐

Minimum mullion split to achieve Building Regs Fire Escape is 605mm using small outer frame and mullion.

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

1	2	3	4	5

Special Requirements:

Ordering Notes:
TOTAL70C = Bevelled System, 5 and 6 chamber options. **TOTAL70S** = Fully Sculptured, 5 chamber system. Frame sizes should be entered as **overall** including add on's and cills. Internally beaded windows are not available with mechanical joints.
Glazing:70mm System: 28mm double glazing or 32mm, 36mm & 44mm triple glazing.
Gasket Types: Security gasket will be fitted as standard to externally beaded windows.
***Spacer Bar:** Bronze as standard or black if warm edge spacer bar required.
±Hinge Types: **Egr** = Egress Hinge (sidehung only) - Add ***EC*** for Easy Clean or ***NC*** for Non Clean
Rest = Restrictor Hinge. If standard hinges are required leave blank.

Important:
Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.
Signed :

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

0252R—Issue 16 01-24