

1-5 Fletchers Square, Temple Farm Ind Estate,  
Sutton Road, Southend-on-Sea,  
Essex SS2 5RN  
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name &amp; Address:

Customer Ref:

Date Required:

Previous Quote No:

Works Order No:

Date Received:

Secured By Design ☐ Doc Q compliant ☐

U Value Compliant: ☐

BFRC Energy Rated: A ☐ B ☐

Authorised Retailer - Energy Rated Product

AR No:  A ☐ B ☐

## FRAME CONSTRUCTION—Internally (dummy sashes will be reqd) or Externally Glazed System

Outerframe: AW604 43x58mm Std Sash: AW686 45mm Int glazed ☐ AW690 45mm Ext glazed ☐ Trans/Mull: AW632 57mm

## GLAZING BEAD/GASKET TYPE \*Bead type determined if int or ext glazed

Bead\*: Square or Bevel Gasket: Black ☐ Anthracite Grey ☐

## FRAME FINISH

White (RAL9910 Std) ☐ RAL:  RAL:  on White ☐






## HANDLE COLOUR

White ☐ Gold ☐ Black ☐ Chrome ☐ Satin ☐ Grey ☐ Enduro Steel ☐

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description	Spacer Bar Colour*	Add on/Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

\*\*Std cill length = frame width +100mm

1	2	3	4	5
 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>

Special Requirements:

## Ordering Notes:

**Glazing:** 28mm glazing as standard **\*Spacer Bar:** Black warm edge spacer bar as standard.  
**Min/Max Heights:** For size limitations see data sheets in the Technical section of our website  
**Transom/Mullion:** AW632 will be used on these windows  
**Cill Height:** 25mm **\*\*Cill sizes available:** 95 / 150 / 190mm  
**Locks:** Shootbolt locking as standard  
**Frame Add On:** 20mm only **Coupler:** 15mm & 26mm available

## Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :