

1-5 Fletchers Square, Temple Farm Ind Estate,  
Sutton Road, Southend-on-Sea,  
Essex SS2 5RN  
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name & Address:  
  
  
  
Telephone:

Customer Ref:  
Date Required:  
Previous Quote No:  
Works Order No:  
Date Received:

Secured By Design  Doc Q compliant   
Part L Compliant Products:   
BFRC Energy Rated Products: A  B   
Authorised Retailer - Energy Rated Product  
AR No:  AR  A  B

**FRAME CONSTRUCTION: Internally (dummy sashes will be required) or Externally Glazed System**    Outer: AW604 43x58mm Std     Sash: AW686 45mm Int glazed  AW690 45mm Ext glazed     Trans/Mull: AW632 57mm


**FRAME FINISH:** White (RAL9910 gloss)\*     RAL:  on White (RAL9910 gloss)     RAL:  on RAL:   \*RAL9910 Gloss is our standard White

**GLAZING BEAD:** \*Bead type determined if int/ext glazed    Square  Bevel     **GASKET TYPE:** Black  Anthracite Grey

**HANDLE TYPE & COLOUR:**    **STANDARD:**  Colour:  *Please see spec sheets on our website for handles styles & colours*  
**CONTEMPORARY:**  Handle Type:  Colour:     Peg & Stay Dummy

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description	Spacer Bar Colour*	Add on/Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from **OUTSIDE** – including Tilt & Turn Windows \*\*Std cill length = frame width +100mm

1	2	3	4	5
 <p>Floating Mullion Req'd <input type="checkbox"/> Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req'd <input type="checkbox"/> Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req'd <input type="checkbox"/> Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req'd <input type="checkbox"/> Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req'd <input type="checkbox"/> Part F <input type="checkbox"/> Compliant Slot Vents</p>

**Special Requirements:** \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Ordering Notes:**  
**Glazing:** 28mm glazing as standard    **Spacer Bar:** Black warm edge spacer bar as standard.  
**Min/Max Heights:** For size limitations see data sheets in the Technical section of our website  
**Transom/Mullion:** AW632 will be used on these windows  
**Cill Height:** 25mm    **\*\*Cill sizes available:** 95 / 150 / 190mm  
**Locks:** Shootbolt locking as standard  
**Frame Add On:** 20mm only    **Coupler:** 15mm & 26mm available

**Important:**  
Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed : \_\_\_\_\_

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.