A	lu-	tec
Windo	& awc	Doors

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

	//	\ 	+	20	O	NDLIX	·	IVI -		LD OAGL		VIIIVDO	• •				L	. 490		
		Alu-			Invoice Name & Address:				Customer Ref:					Secured By Design Doc Q					mpliant [
Windows & Doors						Date Required:				Part L Compliant Products:										
1-5 Fletchers Square, Temple Farm Ind Estate, Sutton Road, Southend-on-Sea,								Previous Quote No:				BFRC Energy Rated Products: B								
Essex	SS2 5RN		20710	^						Works Order No:				Authorised Retailer - Energy Rated Product						
Tel: (01702) 899440 Fax: (01702) 307180 Telephone:						Date Received:					AR No: AR B									
FRAN will b	ME CONSTRU e required) o	ICTION: Interr r Externally G	nally (d lazed S	ummy sas System	shes O	uter: AW605	53x58r	nm 🔲	AW601 53x70mm	Sash: AW	614 45mm Int (glazed	AW611 56n	nm Ext g	glazed [Tr	ans/Mu	ıll: AW63	32 57mm	
FRAME FINISH: White (RAL9910 gloss)* RAL: on White (RAL9910 gloss) RAL: on RAL: *RAL9910 Gloss is our standard V										ndard White										
GLAZ	ING BEAD:	Bead type dete	ermined	l if int/ext o	<i>glazed</i> Sq	uare 🔲 B	evel] GA	SKET TYPE: Blac	k 🔲 Anthrac	ite Grey 🔲									
HAN	DLE TYPE	STANDARD:	□ c	olour:									Please see s	spec shee	ets on our	website	for hand	dles styles	& colours	
& CC	DLOUR:	CONTEMPOR	RARY:	Han	dle Type:				Colou	r:										
	O/All Siz	Size		Design	Mullion	Transom	Glazing		- Glass Des	porintion	Spacer Bar	Add on/	Cill	Cil	, <u>Н</u>	linge 1	Туре	Hinge	Part F Slot Veni in 73mm	
Item	Width	Height	Qty	No.	Break	Drop	U/G	D/G	(see note re la		Colour*	Coupler	Туре	Lengt		gr	Rest	Guard	in 73mm Head	
1																				
2																				
3																				
4																				
5																				
•		•				View	all Wir		from OUTSIDE –	including Tilt 8	Turn Windo	ws		**S	td cill ler	ngth =	frame v	vidth +100	0mm	
1				2				3			4				5					
Floating Mullion Reqd Floatin			llion			Floating Mullion Reqd	Floa Mulli Req							M	loating Iullion leqd					
		Part F Comp Slot V	liant			Cor	t F mpliant t Vents			Part F Compliant Slot Vents			Part F Comp Slot V	liant				C	art F ompliant lot Vents	

ORDER FORM - CHAMFERED CASEMENT WINDOW

Special Requirements:		

Ordering Notes:

Glazing: 28mm glazing as standard. 26.8mm glazed units to be used if laminated glass reqd Glazing: 28mm glazing as standard. 26.8mm glazed units to be used it laminated glass requ

*Spacer Bar: Black warm edge spacer bar as standard.

Min/Max Heights: For size limitations see data sheets in the Technical section of our website

Transom/Mullion: AW632 will be used on these windows

Cill Height: 25mm **Cill sizes available: 95 / 150 / 190mm

Locks: Shootbolt locking as standard

Frame Add On: 20mm. 40mm available for 70mm system only. Coupler: 15mm & 26mm available

Defore ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Page

οf

Signed:

0325ALCH—Issue 6