A	lu-tec
Windo	ows & Doors

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

		Mari.	_+c		O	RDER	FOR	M - (	CONTEMPO	ORARY (	FLAT) C	ASEM	ENT W	/INDOV	V	L	Page	of
Alu-tec				Invoice Name & Address:				Customer Ref:			Secured By Design							
Windows & Doors							Date Required:				Part L Compliant Products:							
1-5 Fletchers Square, Temple Farm Ind Estate,									Previous Quote No:				BFRC Energy Rated Products: B					
Sutton Road, Southend-on-Sea, Essex SS2 5RN								Works Order No:				Authorised Retailer - Energy Rated Product						
Tel: (01702) 899440 Fax: (01702) 307180			Telephone:				Date Received:			AR No: AR B								
EDAN	FRAME CONSTRUCTION: Internally (dummy sashes will be required) Outer: AW605 53x58mm AW604 43x58mm Sash: AW685 45mm Flat T Sash Transom / Mullion: AW632 57mm																	
FRAME FINISH: White (RAL9910 gloss)* RAL: on White (RAL9910 gloss) RAL: on RAL: on RAL: *RAL9910 Gloss is our standard White																		
GLAZING BEAD: Square GASKET TYPE: Black Anthracite Grey																		
HANDLE TYPE STANDARD: Colour: Please see spec sheets on our website for handles styles & col										les & colours								
& C(	LOUR:	CONTEMPO	DRARY: [	Handl	e Type:				Colou	r:			Peg & S	Stay Dummy				
	O/All Siz	ize		Design	Mullion	Transom	Glazing				Spacer Bar Add o	Add on/	/ Cill	Cill	Hinge	Туре	Hinge	Part F Slot Vent in 73mm
Item	Width	Height	Qty	No.	Break	Drop	U/G	D/G	Glass Des	cription	Colour*	Coupler	Туре	Length**	Egr	Rest	Guard	in 73mm Head
1																		
2																		
3																		
4																		
5																		
						View	≀ ≀all Wiı	ndows	from <b>OUTSIDE</b> –	including Tilt 8	k Turn Windo	ws 		**Std ci	l length	= frame v	width +100	)mm
1				2				3			4			5				
Floating Mullion Reqd			Floating Mullion Reqd				Mullion Mul			Floati Mullid Reqd					lullion			
Part F Compliant Slot Vents			Part F Compliant Slot Vents					Compliant Cor			Part F Comp Slot V	oliant	Part F Complia Slot Ve					

S	Special Requirements:		

## **Ordering Notes:**

Glazing: 28mm glazing as standard \*Spacer Bar: Black warm edge spacer bar as standard.
Min/Max Heights: For size limitations see data sheets in the Technical section of our website
Transom/Mullion: AW632 will be used on these windows
Cill Height: 25mm \*\*Cill sizes available: 95 / 150 / 190mm
Locks: Shootbolt locking as standard
Frame Add On: 20mm only Coupler: 15mm & 26mm available

## Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed:

0325ALCO—Issue 4 0-24