A	lu-	tec
Windo	ows & E	Doors

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

		\li.	+		0	RDER	FOR	M - 9	STEEL REF	PLACEM	ENT CAS	SEME	IIW TV	<b>NDON</b>	V	(	Page	of
	ORDER FORM - STEEL RE Invoice Name & Address:								Customer Ref: Secured By Design Doc Q of							oc Q co	mpliant 🗌	
Windows & Doors							Date Required:  U Value Compliant:											
1-5 Fletchers Square, Temple Farm Ind Estate, Sutton Road, Southend-on-Sea,						Previous Quote No:			uote No:	BFRC Energy Rated								
Essex SS2 5RN								Works Order No:				Authorised Retailer - Energy Rated Product						
Tel: (01702) 899440 Fax: (01702) 307180				Telephone:					Date Received:				AR No: AR A B					
												(2) 1=00						
Outer									/) or Externally G	Trans/Mull: A			Square or I			ack  A		or ext glazed e Grev
													HANDLE	ı				,
Whit	e (RAL9910 S	std)   RA	.L:	FRAI	ME FINISH	RAL:			on White	White	Gold   E	Black 🔲	Chrome			Grey 🔲	Endur	o Steel
$\overline{}$	O/All Siz	· — I	Ι		<u> </u>	<u></u>	Glaz	zina	<i></i>					<u> </u>		ge Type		<u> </u>
Item	Width	Height	Qty	Design No.	Mullion Break	Transom Drop		D/G	Glass Des	scription	Spacer Bar Colour*	Add on/ Coupler	Cill Type	Cill Length			Hinge Guard	Slot Vent in 73mm Head
1			<u> </u>							<u> </u>								
			-								1							-
2												$ \times $						
3																		
4																		
5																		
						View	all Wir	ndows	from <b>OUTSIDE</b> –	including Tilt	& Turn Windo	ws		**St	d cill lengt	h = frame v	width +10	0mm
1				2				3			4				5			
		Floati Mullio Reqd	n			Floa Mull Req				Floating Mullion Reqd			Floatin Mullior Reqd	ı̈́Ι			FI M R	oating ullion eqd

Special Requirements:					

## Ordering Notes:

Glazing: 28mm glazing as standard \*Spacer Bar: Black warm edge spacer bar as standard.

Min/Max Heights: For size limitations see data sheets in the Technical section of our website

Transom/Mullion: AW632 will be used on these windows

Cill Height: 25mm \*\*Cill sizes available: 95 / 150 / 190mm

Locks: Shootbolt locking as standard Frame Add On: 20mm only Coupler: 15mm & 26mm available

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed:

0325ALSR—Issue 2 09/19