

BY NAME AND BY DESIGN

Introducing our latest innovation, the Iconik. Inspired by the mantra 'less is more,' this bifold door system has been meticulously designed to offer the least frame, with the slimmest sightlines on the market. Coupled with more light and comfort through its larger glazed areas, high-performing insulation, and smoothly operating half rollers.



NEXT GENERATION DESIGN

With slim 87mm interlocks and U-values as low as 1.3 (double glazed) achieved through advanced weather-lock seals, IconiK delivers maximum energy-efficiency alongside its modern, slim aesthetic. IconiK is available in both Slim and Standard frames, and as a bifold, double door and single door, ensuring the slim sightlines and effortless style are mirrored throughout the exterior.

Product information

| U-Value (Double Glazing) (Ug: 1.0 W/m²K) | 1.3 W/m ² K |
|-------------------------------------------------------|------------------------|
| U-Value (Triple Glazing) (Ug: 0.7 W/m ² K) | 1.0 W/m ² K |
| System Depth | 80 mm |
| Maximum Door Leaf Size (mm) | 1200 w x 3000 h* |
| Maximum Door Leaf Weight | 130 kg |
| Glazing Options | Double / Triple Glazed |
| Glazing Thickness | 23 - 46 mm |

SAFE AND SOUND

Made to withstand the worst of the British weather as well as boasting concealed locks and security hardware for extra peace of mind.

U-Value

1.3

W/m²K

Double Glazing

U-Value

1.0
W/m²K
Triple Glazing

1200mm X 2400mm

Slim Sightlines

